

11-TR08

PRODUCT DESCRIPTION

PRODUCT FEATURES

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE WIDTHS

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

HIGH GRADE TRANSFER ADHESIVE TAPE

Heavy weight, clear transfer adhesive combining exceptional long term bonding performance with a high initial tack. This product is the perfect option for mounting high performance graphics.

High coat-weight
Exceptional temperature resistance
Moisture stable liner for added stability
Available in large format sheets
UL approval to UL969 for marking and labeling systems

Acrylic

0.125mm

Clear

PC Printed Kraft Paper 120gsm

High

Very High

-30°C to 200°C

10°C

3mm – 1000mm

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Nameplates, graphic overlays and membrane switch applications where a free film acrylic laminating adhesive is required. Applications that require long term 'holding power' and environmental resistance.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC122 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01