

11-TR09

PRODUCT DESCRIPTION

PRODUCT FEATURES

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE WIDTHS

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

RUBBER BONDING TAPE - 0.4MM

The original correx bonding tape for estate agent boards. This product is also used in a wide variety of other applications due to its high initial bond and heavy coat-weight of adhesive.

Not suitable for extended outdoor use
Bonds well to LSE substrates
Used for manufacture of Estate Agent boards
Used for manufacture of leather goods

Hot-melt Rubber

0.4mm

Hazy

White Glassine Paper 90gsm

Very High

Low

300%

-20°C to 55°C

20°C

19mm, 25mm, and 38mm

Rolls and pads

1 Year stored at 21°C, 50% RH and out of direct sunlight

Estate agents board manufacture, leather goods, bonding textiles and fabrics during assembly. Bonding the most difficult substrates.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC123 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01