

11-TRR02

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE WIDTHS

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

REINFORCED RUBBER BONDING TAPE - 0.3MM

This toughened rubber reinforced bonding tape is excellent for bonding textured substrates. Its adhesive mass makes it suitable for bonding to textured surfaces.

Good initial bond strength
Excellent bond to rubber and other LSE substrates
Toughened rubber adhesive gives excellent shear strength
Suitable for uneven and textured surfaces

Scrim reinforcement

Modified Rubber

0.30mm

Hazy

White Glassine Paper 65gsm

Very High

High

-20°C to 60°C

20°C

3mm - 1200mm

Rolls

1 Year stored at 21°C, 50% RH and out of direct sunlight

Bonding rubbers, textiles, leather and fabrics. Bonding machine labels to powdered coated surfaces. Estate agent boards.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC127 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01