

## 11-TRR05

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

#### CARRIER

#### ADHESIVE TYPE

#### TOTAL THICKNESS

#### ADHESIVE TAPE COLOUR

#### RELEASE LINER

#### PEEL ADHESION

#### SHEAR STRENGTH

#### CONTINUOUS TEMP. RANGE

#### MINIMUM APPLICATION TEMP.

#### AVAILABLE WIDTHS

#### AVAILABLE FORMATS

#### SHELF LIFE

#### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## LSE ACRYLIC REINFORCED TRANSFER TAPE

A modified polyacrylic adhesive with a scrim reinforced carrier. It exhibits very high initial bond strength and excellent long term holding.

The adhesive mass allows bonding to textured and uneven surfaces while its chemistry gives exceptional temperature resistance.

Very high initial bond strength

Bonds well to LSE substrates

Bonds well to textiles and foams

Excellent temperature resistance

Low VOC and fogging

PET Scrim

Modified Polyacrylic

0.100mm

Hazy

Amber Glassine Paper 90gsm

High

Medium High

-40°C to 140°C

15°C

3mm – 1500mm

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Lamination of foams, rubber and fabrics. High temperature bonding of LSE materials including engineering plastics.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC129 | Issue 3 | Sept 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01