

12-TS04

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

PREMIUM EXTERIOR GRADE TISSUE TAPE

A high coat-weight double sided tape with 12gsm tissue reinforcement carrier. The solvent acrylic adhesive has a very high initial tack along with good dynamic & static shear strength.

High tack modified solvent acrylic adhesive
High temperature resistance
Moisture stable liner
Excellent UV & chemical resistance including most mineral oils, greases, fuels, aliphatic solvents, dilute acids and alkalis, and salts.
Suitable for external use
Available in 3mm - 1040mm widths.

12gsm Tissue

Modified Solvent Acrylic

0.115mm

Hazy

White MS Kraft Paper 120gsm

High

High

2%

-20°C to 150°C

10°C

Rolls, sheets, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Nameplates, engraving laminates, membrane switch panels, directional signage including fire-route marking. Bonding foams and fabrics in high temperature applications.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

