

13-FL12

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE FORMATS

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

FILM TAPE

High performance synthetic rubber adhesive exhibits exceptional tack and peel strength. The high coat-weight on both sides enables it to key into textured surfaces.

Very high initial tack
Excellent bond to LSE surfaces
Soft adhesive flows well into fibrous substrates
Excellent bond properties to low density foams
Excellent bond properties to porous substrates
Available in 3mm - 1000mm widths.

Polypropylene

Synthetic Rubber

0.14mm

Hazy

Blue/Green Supercalendered Glassine Paper 90gsm

Very High

Medium

70%

-40°C to 55°C

15°C

Logs, rolls, sheets, discs, pads, and die-cut shapes

Bonding thin plastic films, fabrics and other flexible substrates. Used extensively for sail-making and other seam reinforcement applications. The ultimate sticks all adhesive.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC108 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01