

## 13-FL13

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

# TECHNICAL DATA SHEET

## PERM/PEEL FILM TAPE

13-FL13 has a clever differential adhesive system. One side has a high tack permanent adhesive and the other side has a medium tack removable adhesive.

Perm/Peel adhesive system  
Clean removal after use  
Conforms to FDA Regulation 175.105 for indirect food contact.  
Resistant to UV, plasticizers and high temperature

### CARRIER

Polyester

### ADHESIVE TYPE

Perm/Peel

### TOTAL THICKNESS

0.05mm

### ADHESIVE TAPE COLOUR

Clear

### RELEASE LINER

White Glassine Paper

### PEEL ADHESION

High/Low

### SHEAR STRENGTH

Medium High/Low

### CONTINUOUS TEMP. RANGE

-25°C to 120°C

### MINIMUM APPLICATION TEMP.

20°C

### AVAILABLE WIDTHS

3mm – 1500mm

### AVAILABLE FORMATS

Logs, rolls, sheets, discs, pads, and die-cut shapes

### SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

### MAIN APPLICATIONS (NOT LIMITED TO)

Promotional posters, temporary holding of materials, flexible removable labels in food industry. Used to hold promotional items, CD's and card into literature and magazines.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

