

## 13-FL04

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

#### CARRIER

#### ADHESIVE TYPE

#### TOTAL THICKNESS

#### ADHESIVE TAPE COLOUR

#### RELEASE LINER

#### PEEL ADHESION

#### SHEAR STRENGTH

#### ELONGATION

#### CONTINUOUS TEMP. RANGE

#### MINIMUM APPLICATION TEMP.

#### AVAILABLE FORMATS

#### SHELF LIFE

#### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## PREMIUM GRADE EXTERIOR FILM TAPE

A double sided, self adhesive tape consisting of a transparent polyester film with a high tack modified acrylic adhesive and a red filmic release liner.

Excellent initial bond strength  
Very good resistance to chemicals, UV and plasticisers  
Suitable for outdoor use  
Red filmic release liner  
Available in 3mm - 1000mm widths

PET Film

Modified Acrylic

0.205mm

Clear

Red PP Film

Very High

Very High

200%

-20°C to 90°C

20°C

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Mounting of moulded plastic parts, LCD screens, rubber/EPDM profiles, fabrics, roller blind assembly, lampshade manufacture, decorative profiles & mouldings in the furniture and automotive industries.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC098 | Issue 7 | Sept 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01