

## 13-FL05

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

#### CARRIER

#### ADHESIVE TYPE

#### TOTAL THICKNESS

#### ADHESIVE TAPE COLOUR

#### RELEASE LINER

#### PEEL ADHESION

#### SHEAR STRENGTH

#### ELONGATION

#### CONTINUOUS TEMP. RANGE

#### MINIMUM APPLICATION TEMP.

#### AVAILABLE FORMATS

#### SHELF LIFE

#### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## FILM TAPE

A transparent double sided self-adhesive tape consisting of a PP film carrier coated with a modified acrylic adhesive. An excellent bond to critical materials such as PP, PE & rough surfaces.

Excellent combination of high initial tack & long-term adhesion  
Good temperature & UV resistance,  
Suitable for outdoor use  
Excellent chemical resistance  
One of the best general purpose bonding tapes  
Available in 3mm - 1250mm widths

Polypropylene

Modified Acrylic

0.22mm

Clear

Amber Glassine Paper 65gsm

Very High

High

200%

-35°C to 80°C

15°C

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Banner hems, mounting rigid plastics, most metals, wood, rubber & foam, heavy decorative materials & displays, signs & scales.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC100 | Issue 4 | Sept 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01