

00-5012

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

DS PET/ACRYLIC ADHESIVE FILM TAPE

A double sided self adhesive tape consisting of a transparent polyester film with a very well balanced modified acrylic adhesive.

Excellent balance of peel, shear and tensile strength
Resistant to elevated temperatures (Up to 200°C)
Very good resistance to chemicals, UV and plasticisers
Approved to UL94 V0
Red PP release line
Available in 3mm - 1370mm widths

PET Film

Modified Acrylic

0.205mm

Glass Clear

Red PP Film

Very High

Very High

200%

-20°C to 100°C

20°C

Logs, rolls, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Mounting of moulded plastic parts, rubber/EPDM profiles, fabrics, roller blind assembly, lampshade manufacture, decorative profiles & mouldings in the furniture and automotive industries, aerospace fit-out.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC099 | Issue 4 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01