

15-VHPB06

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

VHPB - 0.64MM GREY AUTOMOTIVE GRADE

A low application temperature Vhpb tape. Provides a good combination of adhesion to low surface energy surfaces, conformability & initial tack. Specially formulated for application in temperatures approaching freezing.

Ford, JLR and VW Approved Vhpb Tape Resistant to moisture and plasticiser Resistant to Ultra violet {UV} light Resistant to abrasion, corrosion Suitable for indoor and outdoor environments Bonds LSE substrates Available in 3mm- 800mm widths Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TOO)

Foamed Acrylic

780 kgm³

Acrylic Foam

0.64mm

Grey

Red Siliconised Film

Very High

Very High

300% +

-30°C to 80°C

0°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

For fabrication using metals, engineering plastics and composites, sign channel to aluminium and PVC, glazing bars, Automotive Trim attachment, structural bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire

CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

