

15-VHPB AB120

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

ADHESION TO ABS (AFTER 3 DAYS)

ADHESION TO STEEL (AFTER 3 DAYS)

ELONGATION AT BREAK

AGEING RESISTANCE (UV)

HUMIDITY RESISTANCE

TEMPERATURE RESISTANCE

MIN. APPLICATION TEMP.

ADHESION TO LSE SUBSTRATES

TECHNICAL DATA SHEET

VHPB – 1.20MM BLACK AUTOMOTIVE GRADE

Automotive grade very high performance bond tape

Visco-elastic acrylic foam core to compensate for different thermal elongation of bonded parts.
Excellent cold shock performance.
Deep black color for enhanced appearance and high design flexibility.
Closed cell acrylic foam core for reliable sealing to prevent water penetration.
High humidity and UV resistance.
Available in 3mm to 1260mm widths.
Applications include permanent exterior mounting of body side mouldings and decorative trims, emblems, spoilers, antennas, and pillar appliques.

Vhpb Viso-elastic

Vhpb Acrylic

1.20mm

Black

Siliconised HDPE Film

24 N/cm

32 N/cm

1400%

Very Good

Very Good

-40°C to 90°C

0°C

Medium

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC160 | Issue 1 | Oct 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01