

14-FM05

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

PERM/PEEL FOAM TAPE

A unique foam tape with a permanent adhesive on one side and a removable adhesive on the other. The product is excellent for temporary holding of displays, graphics and merchandising.

Perm/peel adhesive system
Conformable foam
Excellent bond to foamex
Clean peel adhesive leaves no residue
Available in 3mm- 1000mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

PE Foam

33 Kg/m³

Perm/Peel

2.0mm

White

White Glassine Paper 65gsm

High/Low

High/Medium Low

60%

-20°C to 60°C

15°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Exhibition graphics and stands, POS and POD items, promotional graphics and temporary hoardings. Temporary holding.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC114 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01