

14-FM01

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION (N/25MM)

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

DOUBLE SIDED FOAM TAPE

14-FM01 is an economical, medium density PE foam coated with an aggressive hot-melt rubber adhesive. It exhibits very high initial tack.

Very high initial tack level
Approved to BS7950:1997 for security glazing
Available in black or white and in thicknesses of 1mm – 25mm
Not recommended for outdoor use or under UV conditions
Available in 3mm- 1000mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

PE Foam

55 kgm³

Hot-melt Rubber

1mm – 25mm

White

Amber Glassine Paper 65gsm

High – Foam Destruction

Medium

250%

-18°C to 60°C

15°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Bonding rigid plastic parts in white goods applications, bonding paper, card and board, Point of Sale and promotional goods. Security glazing applications.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC111 | Issue 7 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01