

14-FM03

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION (N/25MM)

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

EXTERIOR GRADE FOAM TAPE

14-FM03 is a low density PE foam tape with an aggressive modified acrylic adhesive. Conforms to BS7116 Glazing.

Aggressive modified acrylic adhesive
Available in black or white
Available from 2mm to 25mm thickness
Suitable for external use
Available in 3mm- 1000mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

PE Foam

33 Kg/m³

Modified Acrylic

2mm – 5mm

Black or White

Amber Glassine Paper 65gsm

High – Foam Destruction

Medium

130%

-18°C to 80°C

15°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Mounting signage, decorative trim, rigid plastic mouldings, wooden mouldings, trim attachment, glazing bars.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC112 | Issue 7 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01