

**1320700**

**PROTECTION FILM - AUTOMOTIVE SERIES**

**PRODUCT DESCRIPTION**

Transparent wheel rim protection film for long-term outdoor exposure. Ideal for protecting sensitive surfaces during transportation. Transparency makes damages easily recognisable.

07

**PRODUCT FEATURES**

- Good UV resistance, can remain on the surface until the arrival at the end customer.
- Good adhesion to painted & chromed finishes
- Reliable bonding during vehicle transportation
- Cost savings due to reduction in rectification & final repair
- Excellent outdoor resistance for more than 8 months
- Effective prevention against brake disk corrosion - particularly after storage at maritime environments
- Reduction of damages caused by vehicle fixation during sea shipment
- Easy to apply, simple, low cost application & removal processes - no polishing after de-masking
- Easy disposal, film & adhesive is environmentally friendly

06

**BACKING MATERIAL**

PE film

**TOTAL THICKNESS**

70 µm

**ADHESIVE TYPE**

Acrylic

**ADHESION TO STEEL**

1.2 N/cm

**ADHESIVE TAPE COLOUR**

Transparent

**ELONGATION AT BREAK**

200%

**TENSILE STRENGTH**

17 N/cm

**UV RESISTANCE**

26 weeks

**EASY TO REMOVE**

Yes

**SUITABLE FOR DIE-CUTTING**

Yes

**PAINT COMPATIBILITY**

Very Good

**RESISTANCE TO CHEMICALS**

Good

**MAIN APPLICATION (NOT LIMITED TOO)**

Wheel Rim Protection during automotive transportation.

05

04

03

02

01

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

