

3640802

PRODUCT DESCRIPTION

PROTECTION FILM CO-EXTRUDED

Black and white, co-extruded triple layer LDPE film with UV stabiliser.

PRODUCT FEATURES

Tough but conformable film
UV stabiliser impregnated film adds outdoor resistance
26 week outdoor exposure
Suitable for ground stainless steel, aluminium (ground and anodised), plastics
Product is not suitable for brass or copper

CARRIER

LDPE

ADHESIVE TYPE

Natural Rubber

TOTAL THICKNESS

0.08mm

ADHESIVE TAPE COLOUR

White/Black

PEEL ADHESION (180° PEEL)

Low

ELONGATION

>300%

CONTINUOUS TEMP. RANGE

40°C

MINIMUM APPLICATION TEMP.

15°C

AVAILABLE WIDTHS

25mm – 1200mm

AVAILABLE FORMATS

Rolls and die-cut shapes

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC092 | Issue 3 | Mar 2019

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01