

## 22-CR02

PRODUCT DESCRIPTION

**PRODUCT FEATURES** 

## TECHNICAL DATA SHEET

## PREMIUM CREPE MASKING TAPE - 80°C

A premium grade crepe masking tape resistant to  $80^{\circ}$ C with instant adhesion and excellent removability after 7 – 10 day masking.

Instant adhesive and excellent removability High grade crepe carrier that resists curling Resistant to 80°C Suitable for Automotive paint applications

SKIN

THICKNESS

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

**ELONGATION** 

ADHESION TO STEEL

TENSILE STRENGTH

**CONTINUOUS TEMP. RANGE** 

SUITABLE FOR EXTERNAL USE

**AVAILABLE WIDTHS** 

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TOO)

Saturated crepe paper

0.125mm

Natural Rubber/Resins

125 µm

Yellow

> 9%

> 2 N/cm

> 27 N/cm

80°C

No

12mm, 19mm, 25mm, 50mm, up to 1200mm

1 Year stored at 21°C, 50% RH and out of direct sunlight

Air drying and oven curing up to 80°C Automotive panel painting 7 – 10 day masking for hand paint, roller, and spray applications

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

