

## 22-PT01

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

#### CARRIER

#### ADHESIVE TYPE

#### TOTAL THICKNESS

#### ADHESIVE TAPE COLOUR

#### PEEL ADHESION

#### BREAKDOWN VOLTAGE

#### ELONGATION

#### CONTINUOUS TEMP. RANGE

#### MINIMUM APPLICATION TEMP.

#### AVAILABLE WIDTHS

#### AVAILABLE FORMATS

### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## HIGH TEMPERATURE PET MASKING TAPE

22-PT01 is an ultra-high temperature, heavy gauge polyester tape coated on one side with a pressure sensitive silicone adhesive.

Resistant to 200°C short term  
Clean removal adhesive  
Strong 50mic PET backing  
Excellent chemical and solvent resistance  
Excellent stability for die-cut shapes to mask intricate areas

Polyester

Silicone

0.080mm

Dark Green

Medium

7 kv

10%+

+180°C

+21°C

3mm – 1200mm

Logs, rolls, sheets, discs, pads, and die-cut shapes

Electrical, powder coating anodising, & chemical masking.  
Silicon wafer protection. Electrical insulating for edge strengthening, fine wire & non-corrosive applications and general purpose coil applications.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC081 | Issue 5 | Jul 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01