

**2301504**

**PRODUCT DESCRIPTION**

**PRODUCT FEATURES**

**BACKING MATERIAL**

**TOTAL THICKNESS**

**ADHESIVE TYPE**

**ADHESION TO POLISHED STEEL**

**ADHESIVE TAPE COLOUR**

**ELONGATION AT BREAK**

**SUITABLE FOR DIE-CUTTING**

**TEMPERATURE RESISTANCE**

**UV RESISTANCE**

**EASY TO REMOVE**

**PAINT COMPATIBILITY**

**RESISTANCE TO CHEMICALS**

**MAIN APPLICATION (NOT LIMITED TOO)**

# PRODUCT DATA SHEET

## STATIC PROTECTION FILM

A non-adhesive PVC protection film designed to protect ultra sensitive surfaces. This static cling film eliminates the possibility of adhesive residue after removal.

- Non-adhesive adhering system
- Conformable film follows dynamic surface contours
- Suitable for gloss paint, chromed plastics and lacquered substrates
- Printable/writable top surface

WARNING: must not be used in high temperature applications.

Calendared PVC

150 µm

Static

0.4 N/cm

Transparent

300% +

Yes

60°C (Film remains dimensionally stable <=3%)

52 weeks +

Yes

Very Good

Medium

Protection of automotive interior trim for transportation. Also used for glass identification and defect identification labels.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC209 | Issue 1 | May 2019

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01