

2110753

AUTOMOTIVE PROTECTION FILM

PRODUCT DESCRIPTION

A highly conformable automotive surface protection film for lacquered surfaces.

07

PRODUCT FEATURES

Highly conformable film
Proprietary coating allows deep drawing
Sensitive adhesive for lacquered substrates
Easy unwind force
Oil resistant

Common uses include:
Lacquered interior finishes, glass and plastic screens
Also used for the protection of metals during severe mechanical processing such as deep drawing, profiling and bending

06

CARRIER

Coated PVC Film

ADHESIVE TYPE

Acrylic

TOTAL THICKNESS

0.075mm

COLOUR

Blue

PEEL ADHESION

Medium

04

ELONGATION

300%

CONTINUOUS TEMPERATURE RANGE

15°C to 60°C

MINIMUM APPLICATION TEMPERATURE

15°C

AVAILABLE WIDTHS

50mm - 1200mm

03

AVAILABLE FORMATS

Rolls, logs, and die-cut parts.

MAIN APPLICATIONS (NOT LIMITED TO)

Suitable for the protection of sensitive surfaces, stainless steel, glass and aluminium during processing, transport and storage. Protection of metal surfaces during severe mechanical processes.

02

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC196 | Issue 2 | Mar 2023

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

01