

15-VHPB07

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

VHPB TAPE – 1.2MM GREY

A low application temp. Vhpb tape, provides a good combination of adhesion to LSE surfaces, conformability and initial tack. Specially formulated for application temperatures approaching freezing.

Application Temperature 0°C
Resistant to moisture and plasticiser
Resistant to Ultra violet (UV) light
Resistant to abrasion, corrosion
Suitable for indoor and outdoor environments
Bonds LSE substrates
Available in 3mm - 450mm widths
Available in logs, rolls, sheets, discs, pads, and die-cut shapes

CARRIER

Foamed Acrylic

DENSITY

780 kgm³

ADHESIVE TYPE

Acrylic Foam

TOTAL THICKNESS

1.2mm

ADHESIVE TAPE COLOUR

Grey

RELEASE LINER

Red Siliconised Film 0.085mm

PEEL ADHESION

Very High

SHEAR STRENGTH

Very High

ELONGATION

900%

CONTINUOUS TEMP. RANGE

-30°C to 80°C

MINIMUM APPLICATION TEMP.

0°C

SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TO)

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars, Automotive Trim attachment, Constructional bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC136 | Issue 8 | May 2024

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01