

14-FM10

HIGH GRADE EXTERIOR FOAM TAPE

PRODUCT DESCRIPTION

14-FM10 is a high density double-sided PE foam tape with high tack modified acrylic adhesive. This tape has been formulated into one of the best performing foam tapes available today

PRODUCT FEATURES

Very good initial bond
Excellent bond to foamex, metal and composites
High density PE foam
Suitable for external use
Available in 3mm- 1000mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

CARRIER

High Density PE Foam

DENSITY

100 Kg/m³

ADHESIVE TYPE

Modified Acrylic

TOTAL THICKNESS

0.8mm

ADHESIVE TAPE COLOUR

White

RELEASE LINER

Light blue PE Liner

PEEL ADHESION (ASTM D-3330)

6.3 N/cm²

DYNAMIC SHEAR (ASTM D-1002)

3.1 Kg/cm²

ELONGATION AT BREAK (ASTM D-3330)

150%

CONTINUOUS TEMP. RANGE

-25°C to 90°C

MAIN APPLICATIONS (NOT LIMITED TO)

Sign mounting and fabrication, kickboards, nameplates, glazing bars, decals, badges, Point of Sale, mirror mounting, trunking, decorative moulding, door frame trim and decorative rail




SHELF LIFE: 1 YEAR STORED AT 23°C, < 85% RH AND OUT OF DIRECT SUNLIGHT

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC336 | Issue 2 | Jan 2024

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

08

07

06

05

04

03

02

01